


FX35 - 1kV



Basic data:

Max conductor temperature: 90°C
Temp. installation: -20-+90°C

Standards:

Conductor IEC 60228
Construction EN60502-1

Application

For fixed installation indoor/outdoors in air and ground
Halogen free

Construction characteristics	
Conductor	7x2,48mm, annealed copper wires
Insulation	Halogen free, UV-resistant XLPE
Longitudinal water blocking	No water blocking
Marking	Amo kraftkabel FX35
Color	Black, but other alternatives available
Fire class	Not flame retardant according to IEC60332-3
Resistance	$R < 0,524 \text{ Ohm/km}$
Maximum conductor temperature	+250°C
Minimum installation temperature	-20°C
Packing	Drum or coil

Article no / E-number	Product	Conductor	Area	Conductor Diameter	Wall thickness	Total Diameter	Color	Weight
			[mm ²]	[mm]	[mm]	[mm]	[-]	[kg/km]
E0621970	FX35	7x2,48	35	7,44	2,0	11,44	Black	370
E0621975	FX35 T500	7x2,48	35	7,44	2,0	11,44	Black	370
E0621976	FX35 T1000	7x2,48	35	7,44	2,0	11,44	Black	370

All illustrations and specifications of weights, size and dimensions are indicative only

amo kraftkabel AB

Kabelvägen 5, SE-360 75 Alstermo

Phone +46 481 50891 Fax. +46 481 50895 www.amokabel.com