



Art	E-nr	Färg	RAL
879AL	7701283	ALUMINIUM	9006
879GR	7701284	GRAFIT	7016
879W	7701285	VIT	9003

Allmän information	
Typ armatur	
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Frostat polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul AC
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	1,95kg / 1,95kg
Förpackning mått [cm]	23x13,5x34
LED	Lumens EDC 57C 8W xxx 230V A FF Ver.1.0 (Produktblad)
Led modul effekt	8W
Armatur effekt	8W
Lumen modul	890lm
Lumen ut	350lm
Led modul effekt	111,3lm/W
Armaturens effekt	43,8lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	50 000h
LED-fotobiologiskt hot	RG0 or RG1
Energieffektivitetsindex (EEI)	A+
Effektfaktor	PF>0,99
THD-faktor	< 20%
Ta nominel:	+25°C
Maximal omgivningstemperatur	-35...+25°C
Inrush current	2,9A/34µs