



Art	E-nr	Färg	RAL
1581AL	7701416	ALUMINIUM	9006
1581GR	7701422	GRAFIT	7016
1581W	7701419	VIT	9003

## Allmän information

Typ armatur	Väggarmatur
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Glas - härdat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Bakkantsdimmer
Netto / Bruttovikt armatur	1,5kg / 1,5kg
Förpackning mått [cm]	21x12,5x9,5
2xLED moduler	Cree Jx3030 3000K no.1805004
Drivdon	Philips Xitanium 7W 0.35A 20V TE SC 230V 12NC
Led modul effekt	6W
Armatur effekt	7,1W
Lumen modul	870lm
Lumen ut	205lm
Led modul effekt	145lm/W
Armaturens effekt	28,9lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	50 000h
Energieffektivitetsindex (EEI)	<b>A++</b>
Effektfaktor	PF > 0,9
Ta nominel:	+25°C
Inrush current	1A/15,2µs
Antal armaturer på automatsäkring	<b>B 10A: 157, B 16A: 250, C 10A: 260, C 16A: 425</b>