



| Art | E-nr | Färg | RAL |
|--------|---------|-------------------|-----|
| 1715GA | 7703535 | GALVANISERAT STÅL | - |

Allmän information

| | |
|-----------------------------------|--|
| Typ armatur | Väggarmatur |
| Material | Front - galvaniserad stål Kropp - lakkert aluminium |
| Diffuser/Avskärmning: | Polykarbonat med optisk struktur, UV stabiliserat |
| Typ ljuskälla | LED modul + driver |
| Ljusstyrning | Bakkantsdimmer |
| LED | Philips Strip OC 0.5ft 550lm 8xx FC HV5 (Produktblad) |
| Drivdon | Philips Xitanium 7W 0,35A 20V TE SC 230V (Produktblad) |
| Led modul effekt | 4W |
| Armatur effekt | 5,3W |
| Lumen modul | 653lm |
| Lumen ut | 347lm |
| Led modul effekt | 163,3lm/W |
| Armaturens effekt | 65,5lm/W |
| ULOR | 0% |
| Färgtemperatur | 3000K |
| Färgbeständighet (McAdam ellipse) | SDCM3 |
| Färgtolkningsindex (CRI/Ra) | 80 |
| Nominell livstid L70/B50 vid 25°C | >70 000h |
| Energieffektivitetsindex (EEI) | A++ |
| Effektfaktor | PF > 0,9 |
| Ta nominel: | +25°C |
| Inrush current | 1A/15,2µs |

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, BIM Revit, BIM ArchiCAD

