



Art	E-nr	Färg	RAL
1392GA	7703539	GALVANISERAT STÅL	-
1392B	7703540	SVART	9005

Allmän information

Typ armatur	Väggarmatur
Material	Front - galvaniserad stål, lackad
Diffuser/Avskärmning:	Polykarbonat med optisk struktur, UV stabiliserat
Andra material	Bakplatta - galvaniserad stål
Typ ljuskälla	LED modul + driver
Ljusstyrning	Bakkantsdimmer
LED	Philips Fortimo LED Strip 0.5ft 550lm 830 FC HV4
Drivdon	Philips Xitanium 7W 0.35A 20V TE SC 230V 12NC
LED modul effekt	4W
Armatur effekt	5,2W
Lumen modul	629lm
Lumen ut	346lm
LED modul effekt	157,3lm/W
Armaturens effekt	66,5lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>70 000h
Energieffektivitetsindex (EEI)	A++
Effektfaktor	PF 0,96
Ta nominel:	+25°C
Inrush current	1A/15,2µs
Antal armaturer p/automatsäkring	B 10A: 157, B 16A: 250, C 10A: 260, C 16A: 425