



Art	E-nr	Färg	RAL
1280AL	7747628	ALUMINIUM	9006
1280GR	7747629	GRAFIT	7016

Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	PMMA, klart
Typ ljuskälla	LED modul + driver
Ljusstyrning	Ej dimbar
Netto / Bruttovikt armatur	11,63kg / 13,46kg
Förpackning mått [cm]	23x22x113
8xLED moduler	Osram PL-MILI-280-830-0.35A-G1
Drivdon	Philips Xitanium 20W/m 0.15-0,5A 54V
Led modul effekt	17,6W
Armatur effekt	20,3W
Lumen modul	2240lm
Lumen ut	1423lm
Led modul effekt	127,3lm/W
Armaturens effekt	70,1lm/W
ULOR	10%
Färgtemperatur (K)	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25 °C	50 000h
Energiklass	A+
Effektfaktor	PF 0,98
Ta nominel:	+25°C
Inrush current	18A/250µs
Antal armaturer på automatsäkring	B 10A: 21, B 16A: 34, C 10A: 35, C 16A: 57