



Art	E-nr	Färg	RAL
1285AL	7747630	ALUMINIUM	9006
1285GR	7747631	GRAFIT	7016

Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	PMMA, klart
Typ ljuskälla	LED modul + driver
Ljusstyrning	Ej dimbar
Netto / Bruttovikt armatur	7,89kg / 9,18kg
Förpackning mått [cm]	23x22x68
Drivdon	Philips Xitanium 20W/m 0.15-0,5A 54V 230V 12NC [420mA]
Led modul effekt	17,9W
Armatur effekt	22W
Lumen modul	2434lm
Lumen ut	1586lm
Led modul effekt	136lm/W
Armaturens effekt	72,1lm/W
ULOR	10%
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
LED-fotobiologiskt hot	RG0 or RG1
Energieffektivitetsindex (EEI)	A++
Effektfaktor	PF>0,98
Ta nominel:	+25°C
Inrush current	18A/250µs
Antal armaturer på automatsäkring	B 10A: 21, B 16A: 34, C 10A: 35, C 16A: 57