



Art	E-nr	Färg	RAL
1360AL	7748317	ALUMINIUM	9006
1360GR	7748318	GRAFIT	7016

Allmän information	
Typ armatur	
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Polykarbonat med optisk struktur, UV stabiliserat
Typ ljuskälla	LED modul AC
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	10,54kg / 12,11kg
Förpackning mått [cm]	25x115x56
2xLED moduler	Lumens LNM/280X30/9W/830/230V
Led modul effekt	18W
Armatur effekt	18W
Lumen modul	1710lm
Lumen ut	962lm
Led modul effekt	95lm/W
Armaturens effekt	53,4lm/W
ULOR	0%
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	50 000h
Energieffektivitetsindex (EEI)	A+
Effektfaktor	PF > 0,99
Ta nominel:	+25°C
Inrush current	108,8mA/500µs
Antal armaturer p/automatsäkring	B 10A: 19, B 16A: 31, C 10A: 32, C 16A: 53