



- PNP
- Normally open (NO)
- 8.00 mm
- Flush (shielded)
- Connector, M12x1-S04



LISTED IND. CONT. EQ. 81U2
for use in the secondary of
a class 2 source of supply



IND. CONT. EQ.
81U2
LISTED

for use in the secondary of
a class 2 source of supply

Environmental - Type 1 Enclosure



General attributes

Approvals / Conformity

CE
cULus
EAC
IEC 60947-5-2
IP67
Yes
■■
Yes
No
II
Yes
GLOBAL
830 a

Basic standard

Enclosure Type per IEC 60529

Function indicator

Operating distance marking

Polarity reversal protected

Power indicator

Protection Class

Short circuit protected

Trademark

MTTF (40°C)

Electrical attributes

Connection type

Eff. operating current Ie

Eff. operating voltage Ue DC

Electrical version

Load capacitance max. (at Ue)

Max. no-load cur. Io undamped

Minimum operating current Im

No-load current Io damped max.

Operating voltage UB max. DC [V]

Operating voltage UB min. DC [V]

Rated insulation voltageUi

Rated short circuit current

Ripple max. (% of Ue)

Switching freq. f max. (at Ue)

Connector
200 mA
24.0 V
DC, direct current
0.500 µF
5.0 mA
0 mA
10.0 mA
30.0 V
10.0 V
250 VAC
100 A
15 %
1000 Hz

Switching function

Switching output
Voltage drop static max.

Normally open (NO)

PNP
2.5 V

Mechanical attributes

Ambient temperature Ta max.
Ambient temperature Ta min.
Assured operating distance Sa
Connector type
Depth
Diameter d1
Eff. operating distance Sr
Housing material
Mech. installation condition
Mounting length
Rated operating distance Sn [mm]
Sensing face material
Surface protection
Tightening torque

70 °C
-25 °C
6.40 mm
M12x1-S04
65.0 mm
M18x1
8.00 mm
CuZn
Flush (shielded)
50.0 mm
8.00 mm
PBT
Nickel-free coating
25 Nm

Remarks

The sensor is functional again after the overload has been eliminated.

Embeddable: See installation notes for inductive sensors with extended switching distance 825357.

For further information on MTTF/B10d, please refer to the MTTF / B10d Certificate.

Specification of the MTTF value and the B10d value do not represent any binding quality and/or life expectancy guarantees.

