

- Female M12
- 90°angle



General attributes

Additional features	Drag chain compatible
Approvals / Conformity	cULus LISTED
Cable jacket color	black
Enclosure Type per IEC 60529	IP68
Function indicator (PIN 4)	No
Power indicator	No

Electrical attributes

Operating voltage UB max. AC [V]	250.0 V
Operating voltage UB max. DC [V]	250.0 V
Rated current (40°C)	4.0 A
Switching function	Normally open (NO)
Switching output	No

Mechanical attributes


Acceleration max. (drag chain)	5 m/s ²
Ambient temp. max. (fixed)	90 °C (UL 80 °C)
Ambient temp. max. (moving)	90 °C (UL 80 °C)
Ambient temp. max.(drag chain)	60 °C
Ambient temp. min. (fixed)	-50 °C
Ambient temp. min. (moving)	-25 °C
Ambient temp. min.(drag chain)	-25 °C
Bending cycles	> 5 Mio.
Bending radius fixed cable	min. 5 x D
Bending radius tensioned cable	min. 10 x D

Cable diameter D	4.3 +/- 0.20 mm
Cable jacket material	PUR
Cable length L [m]	5.00 m
Conductor cross-section	0.34 mm ²
Connector configuration	90°angle
Connector type	M12x1
Connector type (Header I)	Female M12
Contact material	CuSn
Cover nut material	GD-Zn
Drag chain compatible	Yes
Grip material	PUR
Number of conductors	3
Number of female/male pins	5
Permiss.horizon. traverse dist	at 5 m/sec ² 5 m
Permiss.vert. traverse dist	at 5 m/sec ² 2 m
System	molded
Tightening torque pigtail	0.6 Nm
Traverse speed max(drag chain)	at 5 m horiz. travel 200 m/min

Additional text

Flame resistant per IEC 332-2
 Halogen-free per IEC 60754-1
 Enclosure type accord. to IEC 60529, when threaded together with the appropriate counterpart.
 Raw Cable Approval UL+CSA, UL-AWM Style 21198 or 20549

- 1 _____
- 2 _____
- 3 _____
- 4 _____
- 5 _____



PIN 1: brown
 PIN 3: blue
 PIN 4: black