技术要求:
1.严格按图纸打印
2.CMYK彩色打印，A4纸.单面印刷
3.如有问题，请及时沟通

if no tolerance on it, see below. For important assembly size, tolerance will be noted in addition.
图中未标注公差的尺寸以下面的公差为准.重要的配合尺寸另标公差

dimension range 尺寸范围	metal/plastic 五金/塑胶	dimension range 尺寸范围	glass/mood/casting/tube 玻璃/木器/铸铁/长管
>0 - 15	± 0.1	>0 - 15	± 0.5
>15 - 50	± 0.15	>15 - 30	± 1
>50 - 100	± 0.25	>30 - 100	± 1.5
>100 - 200	± 0.4	>100	± 2
>200 - 400	± 0.6	thread & thickness according to standard 螺纹.材料厚度按标准做	
>400	± 1	unit 单位	MM

Product Name 产品名称	DI174客户说明书 P-1602530B		
Model No. 工厂型号	TC36052		
Drawing By 设计		Scale 比例	1:1
Check By 审核		Material 材质	80g
Approve By 核准		Rev. 版本	A0
		Sheet 页码	1 OF 1
Drawingsize 图纸尺寸	A4		

Diaman LED commercial lighting
东莞市达恩照明有限公司
Dongguan Diaman International Limited

Finish 表面处理	
Part Name 物料名称	说明书
Erp No. 物料编码	611AS5157001
Drawing No. 图号	SM5157

DESIGNLIGHT
SCANDINAVIAN AB

Art nr: P-1602530B
E-nr: 74 657 09

Effekt Power	Material Material	Färgtemperatur Color temperature	Armaturfärg Fixture color	Anslutning Connection	Ljusflöde Louminus Flux
7W	Aluminium	3000K	Black	230V	590 lm

CE, RoHS, IP CERTIFIED BY SGS

LED | LED Driver 1x7W 350mA | 590 lm | 1044 cd | L70 | 24/36/64° | IP20 IP21 | 79mm | H 39 mm | 90mm | 40.000 | CE | RoHS | Färg temp. 3000K

- Dimbar med 350 mA driver
- 84 lm/w med lins, driver
- 118 lm/w utan lins, driver
- CRI Värde >85

- Dimmable with 350 mA driver
- 84 lm/W with lens, driver
- 118lm/W without lens, driver
- CRI value > 85









1. Stäng av strömmen/Turn off the power



2. Borra hål i taket/Drill hole in ceiling



3. Anslut till LED-drivern/Connect to LED driver



Mått/Dimension



DESIGNLIGHT
SCANDINAVIAN AB

Designlight Scandinavian AB | Toffelvägen 1 | SE-342 60 Moheda
Kundcenter: Telefon 0472-716 10 | Fax 0472-716 09 | info@designlight.nu | www.designlight.nu



Komihåg vid montering av downlight LED

Kontrollmät **ALLTID** diametern före håltagning i tak. Antal watt per lampa x antalet lampor ger storleken på transformator. Vid installation av LED följ **ALLTID** kopplingschema.

OBS! Det är olika transformatorer på LED och halogen.

- 1-2W/kvm vid mjukare belysning normal takhöjd.
- 3-4W/kvm vid allmän belysning normal takhöjd.

LED är:

- Miljövänlig och energisnål.
- Lång livslängd, 20.000-50.000 timmar.
- Låg värmeutveckling, stötsäker.

Trivs bäst i kyla, ju lägre temperatur och god luftarea desto bättre ljuseffekt. För ökad livslängd på LED-lampor bör armaturer med kylfläns användas.

Tänk på att **ALDRIG** montera downlight direkt mot lättantändligt material. Desto mer luftarea runt den monterade downlighten, desto säkrare blir installationen. Ökad luftarea ger längre livslängd på ljuskälla och armatur.

Things to remember when installing LED downlights

ALWAYS measure the diameter prior to perforation in ceiling. The amount of Watt per light times the number of lights equal the size of transformer. During installation of LED, **ALWAYS** adhere to the circuit diagram.

N.B. Transformers differ for LED and halogen.

- 1-2W/square meter for softer lighting and standard ceiling height.
- 3-4W/square meter for ambient lighting and standard ceiling height.

LED is:

- Environmentally friendly and energy efficient.
- Long life expectancy, 20 000-50 000 hours.
- Low heat generation, shock resistant.

LED lights perform at best in cold, the lower the temperature and the more air volume, the better the light output. For increased longevity on LED lights, fixtures with heat sinks should be used.

Remember to **NEVER** install a downlight directly adjacent flammable materials. Sufficient air volume surrounding the installed fixture provides a safer installation. Increased air volume increases life expectancy for both light source and fixture.

www.designlight.nu

Drawing Revision history
变更记录
Description 修改内容

REV 版本	Mark 标记		By 修改人	Date 日期